

VX-246

Heavy Duty Licence Free PMR446 Radio

A Tool for Professionals

- World First – Full 16 Key DTMF Keypad PMR446 Radio
- Easy to use CTCSS and DCS
- Paging Facility *
- Voice Encryption *
- *Requires optional FVP-25



Actual Size

Supplied Accessories



FNB-83
7.2 V 1400 mAh
Ni-MH Battery Pack



VAC-10C/U*
3 hr Desktop Rapid Charger
*C:230-240 VAC
U:230 VAC with UK plug

VX-246 UHF FM PMR446 Radio

16 Channel Heavy Duty PMR446 Radio from Yaesu

The Yaesu VX-246 heavy duty PMR446 transceiver provides 500 mW ERP of power for reliable two-way communications within a two-mile radius depending upon terrain.


Lock out interference and annoying breakthrough from other stations on the same channels by choosing from one of 38 CTCSS tones or from one of 104 DCS sequences on one of the 8 preprogrammed RF channels in the PMR446 allocated frequency range. Up to 16 different channel / CTCSS or DCS sequences can be programmed into the radio.

The radio can be programmed using the front panel keypad, and cloned from another VX-246 using the CT-27 cloning cable kit.

The FVP-25 voice encryption and paging option uses simple speech inversion techniques to keep your conversations private, and provides selective calling using DTMF paging. The VC-25 VOX headset enables handsfree operation of the VX-246.

Built by Vertex Standard, one of the worlds leading manufactures of professional communications equipment, the VX-246 is both small, rugged (MIL Spec Rated), lightweight and ideal for business, industry or recreational use.

Another Functions : •Keypad Locking •TOT (Time Out Timer)
•RX Power Save •Low Battery Indicator



SPECIFICATIONS	
Frequencies: 8 Channel in PMR 446 allocated channels 446.00625 MHz~446.09375 MHz	Sensitivity: 0.25 μV @ 12 dB SINAD 0.8 μV emf @ 20 dB SINAD
TX Output Power: 500 mW ERP	Case Size: 58 x 108 x 26 mm (WxHxD)
Battery Life: 24 Hours for FNB-83 (SAVE ON) (RX:TX:STBY 5/5/90 duty cycle)	Weight : Approx. 323 g (w/FNB-83)
Operating temp. range: -20° C to +55° C	Accessories Supplied with the VX-246 FNB-83 7.2 V 1400 mAh Ni-MH Battery Pack VAC-10C/U* 3 hr Desktop Rapid Charger
Specifications subject to change without notice or obligation.	

*C:230~240 VAC U:230 VAC with UK plug

Options		
<p>MH-45B4B Speaker Microphone</p>	<p>FVP-25 Encryption / DTMF Pager Unit</p>	<p>FBA-25A Alkaline Battery Case for 6AA-Size Cells</p>
<p>MH-37A4B Earpiece Microphone</p>	<p>VC-25 VOX Headset</p>	<p>CT-27 Radio to Radio Cloning Cable</p>

About this brochure: we have made this brochure as comprehensive and factual as possible. We reserve the right, however, to make changes at any time to equipment, optional accessories, specifications, model numbers, and availability. Some accessories shown herein may not be available in some countries. Some information may have been updated since the time of printing; please check with your Authorized Yaesu Dealer for complete details.

YAESU VERTEX STANDARD CO., LTD.
4-8-8 Nakameguro, Meguro-ku, Tokyo 153-8644, Japan

VERTEX STANDARD <http://www.vertexstandard.com>
Email: amateursales@vxstdusa.com
US Headquarters
10900 Walker Street, Cypress, CA 90630, U.S.A.
Phone 714/827-7600; Fax 714/827-8100

For the latest Yaesu news, visit us on the Internet:
<http://www.vxstd.com>

YAESU EUROPE B.V.
P.O. Box 75525, 1118 ZN Schiphol, The Netherlands

YAESU UK LTD. <http://www.yaesu.co.uk>
Email: sales@yaesu.co.uk
Unit 12, Sun Valley Business Park, Winnall Close
Winchester, Hampshire, SO23 0LB, U.K.

VERTEX STANDARD HK LTD. <http://www.vxstd.com.hk>
Unit 5, 20/F., Seaview Centre, 139-141 Hoi Bun Road,
Kwun Tong, Kowloon, Hong Kong